
ATS3500AV-IP-MBC

Advisor Advanced 3500 IP panel VdS motherboard card



ATS3500AV-IP-MBC

Advisor Advanced 3500 IP panel VdS motherboard card

Technical specifications

System

Product line	Advisor Advanced
Product type	Integrated Access Control
Panel type	Hybrid
Kit	No
No. of keypads / readers	16
Data Gathering Panels (DGP)	15
No. of alarm groups	16
Specified cable	WCAT52 / WCAT54 or equivalent

Inputs

Max no. of inputs	32
Onboard inputs	8
Inputs plug-in expansion	8

Outputs

No. of outputs	128
No. of onboard outputs	5

Area

No. of areas	8

User/Cards

Max. no. of users	more than 2000
Users with name	1000
Max. no. of cards	2000 to 65532
Max. no. of PIN codes	2000 to 65532

Access control

Standard doors on control panel	8
Door groups	128

Communication

Onboard transmission type	IP
Transmission extension	GSM, GSM/GPRS, GSM/GPRS/IP, PSTN
Databus type	RS485

Event log

Alarm event log	14500
Access event log	10000

Electrical

Power supply type	230 VAC
Mainboard current consumption	150 mA
Max system current	1950 mA at 13.8 V ±0.2 V
Max aux power current	450 mA (depends on backup power needs)
Auto-reset fuses	5

Physical

Physical dimensions	202 x 90 x 40 mm
Housing	No housing

Environmental

Operating temperature	-10 to +55°C
Relative humidity	95% noncondensing

Regulatory

Compliancy	CE
Certification	CE, VdS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 15:14