FF-AP1N

Air Purge for FF7x series

Application

The Air Purge kit is intended to be mounted in between a Flame Detector (FF7x series - Non Exd versions) and adjustable mounting bracket (FF705), with the Air Purge kit nozzle positioned to channel air from the inlet onto the window of the flame detector to prevent obscuration by particles.

Successor of FF-AP1



Mounting

The Air Purge nozzle must be angled at 30° from horizontal in order to maximize the air flow over the front window.

Installation

The purge air adapter should be connected to an external air supply via the female 1/4” BSP non return valve.

The air should be oil free and dry with a pressure range from 7psi (0.5Bar) to 50psi (3.5Bar).

If the air is not required continuously to keep the viewing window clean then a pulse of air can be supplied at regular intervals.

Caution: This product is not suitable for use in ATEX zone 0 - For use in ATEX zone 1/21 or 2/222, air must be clean and the system blown through before placing in a hazardous environment

FF-AP1N

Air Purge for FF7x series

Technical specifications

Physical

Mounting type	Screw / bolt mount

EDWARDS
Built for Resilience

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 6 December 2024 - 9:05