BS129NS3

Batterie, 12 V, 26 Ah (pour centrales et alimentations NFA2P CD150, ATS2402, 3402, 4602,1204)



BS129NS3

Batterie, 12 V, 26 Ah (pour centrales et alimentations NFA2P CD150, ATS2402, 3402, 4602,1204)

Spécifications techniques

General

Product type	Sealed lead acid battery

Electrical Characteristics

Nominal voltage	12 V
Nominal capacity	26 Ah
Internal approx. resistance	10 mOhm

Charge / discharge

Max. charge voltage	13.8 VDC at +20°C
Max. charge current	7.8 A
Max. discharge current	130 A

Temperature

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

Physical

Material	ABS
Terminal type	MS bolt & nuts

Environmental

Fire retardant	Yes
Storage temperature	-15 to +50°C

Regulatory

Compliancy	CE, RoHS 2, WEEE
Certification	NFA2P

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57