# DDV1016AM-D

**16m 50ft Dual 9C AM VdS/EN Grade III**



# DDV1016AM-D

## 16m 50ft Dual 9C AM VdS/EN Grade III

## Spécifications techniques

### General

| | |
|---|---|
| Technology | Double |
| Application type | Fixation murale |
| Anti masking | Yes |
| Pet immune | No |
| Camera | No |
| Pry-off tamper kit | Embarqué |

### Detection

| | |
|---|---|
| Max. detection range | 16 m |
| Microwave frequency (nom.) | 5.8 GHz |
| Undercrawl protection | Yes |
| Alarm memory | Yes |
| Alarm time | 3 secondes |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Verdrahtet |

### Inputs/outputs

| | |
|---|---|
| Remote control lines | Jour/Nuit, Test de fonctionnement |

### Physical

| | |
|---|---|
| Colour | Weiß |
| Mounting height | 2 to 3 m |

### Environmental

| | |
|---|---|
| Environment | Drinnen |

### Regulatory

| | |
|---|---|
| EN50131 grade | Grad 3 |
| Certification | EN50131 Grade 3, VdS |

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web fr.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57