# DD1012AM-D

**16m 50ft Dual 9C AM VdS/EN Grade III**



# DD1012AM-D

## 16m 50ft Dual 9C AM VdS/EN Grade III

## Technische specificaties

### General

| | |
|---|---|
| Technology | Dual |
| Application type | Montaje en pared |
| Anti masking | Yes |
| Pet immune | No |
| Camera | No |
| Pry-off tamper kit | On board |

### Detection

| | |
|---|---|
| Max. detection range | 16 m |
| Detection range | 12 m |
| Microwave frequency (nom.) | 5,8 GHz |
| Undercrawl protection | Yes |
| Alarm memory | Yes |
| Alarm time | 3 sec |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Kablede |

### Inputs/outputs

| | |
|---|---|
| Remote control lines | Día/Noche, Prueba de paseo |

### Physical

| | |
|---|---|
| Colour | Hvid |
| Mounting height | 2 to 3 m |

### Environmental

| | |
|---|---|
| Environment | Indendør |

### Regulatory

| | |
|---|---|
| EN50131 grade | Lønklasse 3 |
| Certification | EN50131 Grado 3, VdS |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57