# ATS1190X4

**Pack 4 Leitores de Proximidade "ATS Smart"- Cabo 2.5m**



# ATS1190X4

## Pack 4 Leitores de Proximidade "ATS Smart"- Cabo 2.5m

## Especificações técnicas

### System

| | |
|---|---|
| Supported card types | HiTag2 |
| Addressing type | Card Addressing, Keypad Addressing, Software Addressing |
| Reader accessory | Optional Color Covers |

### Technology

| | |
|---|---|
| Reader type | Proximity, Smart Card |
| Reader operating-transmitting frequency | 125 KHz |
| Supported technology 125 kHz | HiTag 2 |

### Interface & connections

| | |
|---|---|
| Interface | ATS RS-485, Wiegand |
| Connector type | Pigtail |

### Inputs/outputs

| | |
|---|---|
| Inputs | Request to exit |
| Outputs | 1 Open Collector (25 mA) |

### Tamper type

| | |
|---|---|
| Pry-off tamper | Yes |

### Operation

| | |
|---|---|
| PIN keypad | No |

### Physical

| | |
|---|---|
| Colour | White |
| Material | Plastic |
| Mounting Type | Surface mount |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Environment | Indoor |

Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57