# UC240

## UltraSync Communicator with IP and 4G/2G dual path suitable for both fire and intrusion panels

### Overview

UC240 UltraSync Communicator is a dual path alarm signalling unit for transmitting alarm signals from a customer's alarm panel to a Central Monitoring Stations (CMS). The monitoring path is based on IP and SIM 4G/2G mobile technology. The unit is designed for use in both security and fire systems.

- Dual-path monitoring for low, medium and high risk sites, covering intruder applications, fire and more.
- These monitored alarm signalling devices are small enough to fit inside most alarm panels. They use two signalling paths – if the primary path is down, the secondary path kicks in. And if that happens, the secondary path will use the primary path reporting and polling times.
- The primary path uses IP technology to send alarm signals over the customer's network or broadband hub.
- The secondary path uses 4G or 2G mobile connectivity – with dual SIMs for extra resilience.
- EN50131 Grade 3 and EN50136 certified for intrusion systems.
- EN54-21 certified for fire alarm systems.

### Alarm panel interfaces

- 16 general purpose alarm inputs (Logic High = +2V to +30V/Logic Low = <1.3V)
- 3 relay outputs
- Unconnected state: Logic Low
- Standard screw terminals
- Programmable function output-for remote control of site devices
- Line fault output-for status indication at site of alarm signalling path
- Dial Capture with phone line simulation
- Onboard RS232 or RS485 for direct panel interface to some panels

### Dial Capture features

- Converts dialler alarm systems into high security signalling devices
- Alarm panel interface supports: Ademco Contact ID, Ademco Hi Speed, Ademco 4+1, Ademco 4+2, SIA 1/2/3

### Configuration

- Simple single push button pin learn
- iOS and Android installer app
- Using on board menu driven by push buttons

# UC240

## UltraSync Communicator with IP and 4G/2G dual path suitable for both fire and intrusion panels

## Technical specifications

### General

| | |
|---|---|
| Product line | UltraSync |

### Network

| | |
|---|---|
| Communicator type | 2G, 4G, Cellulare, IP |
| GSM frequency | LTE: Penta-Band 700 (Bd28) / 800 (Bd20) / 900 (Bd8) / 1800 (Bd3) / 2100 MHz (Bd1) + GPRS Dual band (900/1800 MHz) |

### Reporting

| | |
|---|---|
| Reporting protocols | Contact ID, SIA |
| Supported receivers | UltraSync |

### Interfaces

| | |
|---|---|
| Ethernet | RJ-45 1000 Mbps Ethernet Interface |
| Antenna | Si, incluso |

### Input/Output

| | |
|---|---|
| Inputs | 16 general purpose alarm inputs |
| Outputs | 3 relay outputs |

### Electrical

| | |
|---|---|
| Operating voltage | 9.5 to 30 VDC |
| Current consumption | 85mA @12 VDC |

### Physical

| | |
|---|---|
| Physical dimensions | 95 x 67 x 17 mm |
| Colour | Sort |

### Environmental

| | |
|---|---|
| Operating temperature | -10°C to +55°C |
| Relative humidity | 5 to 75% |
| Environment | EN50130-5 ; Classe II - Da interno (generale) |

### Regulatory

| | |
|---|---|
| Certification | EN50131 Grade 3, EN50136, EN54-21 |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 June 2026 - 15:33