# AS700G3

## Outdoor siren, plastic housing, NFA2P Grade 3

### Product overview

The outdoor siren is a signaling device to alert others if an emergency arises. It is a very important addition to a security system as it ensures everyone on site knows about the alarm system activation.
This siren has coated electronics and IP44 rated for a variety of applications, especially in harsh environments.
Designed to comply against EN Grade 3 certification, the siren includes an enhanced protection against sabotage.
The battery and power supply are fully supervised.

As soon as an intrusion is detected, the outdoor siren triggers a powerful 105 dB sound signal.
Its sound and duration can be programmed and its battery has up to 60 hours autonomy.



### Details

- Battery circuit protection with resettable fuse
- Enhanced tamper protection
- Aritech elegant design
- Self test every 24 hours to check the integrity of the battery and its charging circuit
- Engineer mode (for commissioning and to inhibit sounder operation)

# AS700G3

## Outdoor siren, plastic housing, NFA2P Grade 3

## Technical specifications

### General

| | |
|---|---|
| Accessory group | Sirene |
| Type | Udendørs sirene |
| Sounder output | >101 dBA at 1m |

### Flash specifications

| | |
|---|---|
| Current consumption | 10 mA @ 13.8 V (quiescent) |

### Electrical

| | |
|---|---|
| Power supply type | 9 VAC |
| Operating voltage | 9 to 15 V |
| Current consumption | 100 mA at 9 to 15 VDC (typical) |

### Physical

| | |
|---|---|
| Physical dimensions | 203 x 260 x 81 mm |
| Net weight | 1130 g |
| Colour | Hvid |
| Material | ABS |

### Environmental

| | |
|---|---|
| Vandal proof | Yes |
| Operating temperature | -10 to 55°C |
| Storage temperature | -10 to 55°C |
| Relative humidity | <95% noncondensing |
| Environment | EN50130-5 ; Classe II - Intérieur (général) |
| IP rating | IP44 |

### Regulatory

| | |
|---|---|
| Compliancy | CE |
| Certification | EN50131 Grade 3 |
| Standards | NFA2P Grade 3 |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 June 2026 - 15:08