TVN-1204CS-4T

TruVision NVR 12, 4 kanały, 4 porty PoE, 40 Mb/s, 4 TB



Szczegóły

- Konfiguracja Plug and Play
- Obsługuje kodowanie H.264, H.265 i H.265+, w zależności od kamer
- Cztery porty Plug & Play PoE (obsługa PoE-af i PoE-at) o maksymalnej rozdzielczości 4K (8MP)
- Automatyczna konfiguracja adresów IP poprzez porty Plug & Play PoE
- Przepustowość nagrywania do 40 Mb/s dla maksymalnie czterech kamer IP
- 4 TB wbudowanej pamięci masowej
- Nagrywanie w czasie rzeczywistym, do 4 MP
- Wyjście monitora HDMI/VGA
- Automatyczne wykrywanie kamery IP TruVision
- Import/eksport konfiguracji kamery IP
- Obsługa UltraSync dla zdalnego dostępu bez przekierowania portów
- Wykrywanie ruchu, VCA, maskowanie prywatności i wykrywanie sabotażu, zależne od wykorzystanych kamer
- Dedykowane wykrywanie osób/pojazdów w połączeniu z obsługiwanymi kamerami
- Obsługa kamer innych firm za pośrednictwem ONVIF Profile S lub RTSP (protokoły niestandardowe)
- Integracja z centralami SSWiN Aritech IP poprzez raportowanie SIA/XSIA
- Obsługa klawiatury IP TVK-600
- Obsługa nagrywarki DVD USB
- Pełny dostęp przez przeglądarkę, menu ekranowe OSD oraz oprogramowanie do podglądu na żywo, nagrań i konfiguracji
- Aplikacja TVRMobile na iOS i Android do zdalnego podglądu
- Obsługa TruVision Navigator

- Integracja zewnętrzna przez SDK

Reasons to choose TVN 12

The TVN 12cS recorder series offers a full-featured, compact recording solution for IP cameras with a maximum resolution of 8 MP(4K).
The TVN-1204cS is a cost-effective, easy-to-use recorder capable of recording up to four IP cameras, connected to the built-in PoE ports or via the LAN network.

Easy to use

A setup wizard with auto detection of IP cameras guarantees a fast installation of the recorder.
The TVN 12cS can be added to the internet without port forwarding or VPN, thanks to the built-in UltraSync connectivity. Showing remote video on mobile applications was never easier.
In combination with dedicated TruVision cameras that can support people and/or vehicle detection, the TVN 12 recorder series can find relevant events faster and without efforts.

Applications

The TVN 12cS is the ideal recording solution for small commercial and residential applications, where ease of use and fast deployment time are important.

TVN-1204CS-4T

TruVision NVR 12, 4 kanały, 4 porty PoE, 40 Mb/s, 4 TB

Specyfikacja techniczna

General

Technology	IP
Operating system	Linux embarqué
Rack mountable	No

Video/audio input

Camera channels	4
IP camera channels	4
Camera bandwidth	40 Mbps
Audio compression	G.711alaw, G.711ulaw, G.722, G.726
Max. IP audio in	4
Max. analog audio In	1
Supported video compression standards	H.264, H.265, H.265+
Supported video streaming standards	Onvif, RTSP protocoles personnalisés

Local viewing

HDMI output	1
HDMI version	1.4, 2.0
VGA output	1
Max. local output resolution	4K
Synchronous playback OSD (channels)	Do 4 kanałów (1080P)

Remote viewing

Total available viewing bandwidth	80 Mbps
Max. live viewing streams	128 strumieni
Max. playback viewing streams	8 strumieni
Max. simultaneous playback web browser	Do 8 kanałów
Reverse playback web browser (channels)	Do 8 kanałów
UltraSync support	Yes, embedded
Software compatibility	Advisor Manager, TruVision Navigator, TVRmobile
Browser compatibility	Google Chrome, Internet Explorer, Mozilla Firefox, Safari

Storage

Storage capacity	4 TB
SATA interfaces	1
Max. capacity per SATA HDD (TB)	8
Maximum recording resolution	4 K
Recording modes	Continuous, Événement, Manuel
External storage	NAS
Edge failover recording	Yes

Networking

Network interface cards (NIC)	1
NIC type	RJ-45 10/100 Mbit/s auto-adaptable interface Ethernet
PoE ports	4
Total PoE budget	50 W
PoE standards supported	PoE-af, PoE-at
Max. PoE budget per port	≤30 W
Plug & Play PoE support	Yes
Flexible PoE allocation	Yes
DNS support	DDNS, ezDDNS, No-IP
HTTPS support	Yes

External interfaces

USB interface back	1
USB interface front	1
Alarm inputs	4
Alarm outputs	1
Max. analog audio outputs	1

Electrical

Operating voltage	48 VDC
Power supply type	48 VDC
Power consumption without HDD (W)	≤65 W

Physical

Physical dimensions	320 x 240 x 48 mm (W x D x H)
Net weight	1.2 kg
Colour	Black

Environmental

Operating temperature	-10 do +55°C
Relative humidity	10 do 90% bez kondensacji

Regulatory

Compliancy	CE, FCC, RCM, REACH, RoHS, UKCA, UL, WEEE

Będąc firmą innowacyjną, Kidde Global Solutions zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 12 November 2026 - 20:20