# PM865

**Boxed power supply, switch mode, 24 VDC, 5 A**




## Details

- Fault and mains present indicators
- Battery disconnect to prevent deep discharge
- Tamperswitch
- Fault outputs
- Mains and dc fuse
- Powder coated steel housing

# PM865

## Boxed power supply, switch mode, 24 VDC, 5 A

## Technische specificaties

### General

| | |
|---|---|
| Fuse(s) | 230 VAC input 3.15A, 12/24V output 5 A |

### Electrical

| | |
|---|---|
| Mains input | 230 VAC |

### Output

| | |
|---|---|
| Power output voltage | 27.6 VDC |
| Output ripple | 100 mV pk-pk max |
| Power output current mains | 5 A |

### Battery

| | |
|---|---|
| Max. Battery capacity | 7.2 Ah (x2) |
| Battery charge current | 1 A |
| Battery recharge time | 20 hours |
| Battery disconnect voltage | 19.6 ±0.2 VDC |

### Physical

| | |
|---|---|
| Colour | Hvid |
| Form factor | Stål kabinet |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 2, WEEE |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57