DT992

Värmedetektor i Discovery 990-serien. Larmindikering LED (röd). 17-28 VDC, 400 µA-3,5 mA, Storlek (Hxdiameter) 42x100 mm, IP44

General

The DT992 is an elegant, slim-line addressable heat detector that provides temperature information to the CIE. It uses a single thermistor to sense the air temperature around the detector. With its 5 operating modes, it supports 5 classes of temperature detectors as stipulated by EN54.

Operating Modes

Every operating mode has a different behaviour, each suitable for a different application. All modes have a fixed temperature trigger, with optional rate-of-rise selection allowing the detector to respond to a temperature alarm before the fixed level is reached. The DT992 supports A1R (57°C with rate-of-rise), A2R (61°C with rate-of-rise), A2S (61°C static), CR (90°C with rate-of-rise) and CS (90°C static) modes of operation.

Unique Addressing

A unique, patented addressing method provides simple, user-friendly and accurate identification of device location. A coded card, inserted in the base, is read by the detector as it is plugged in. All the electronic components are in the detector, but the location information is held in the base. Addressing errors during maintenance are eliminated because the address remains in the base. Pre-coded and pre-numbered address cards are available.

Applications

The DT992 is ideal for use in environments that are dirty or smoky under normal conditions. It is therefore well suited installation in warehouses, loading bays and car parks.



Detaljer

- 5 Approved response modes for ease of optimistation to different environments
- Rejection of transient signals
- Drift compenstation to ensure constant sensitivity
- 360° alarm visibility
- Flashing LED option
- Fast alarm reporting
- EN54 approved and CPR certified

DT992

Värmedetektor i Discovery 990-serien. Larmindikering LED (röd). 17-28 VDC, 400 µA-3,5 mA, Storlek (Hxdiameter) 42x100 mm, IP44

Tekniska specifikationer

Physical

Colour	Hvid
Mounting type	Montaggio su base
Material (body)	Polycarbonat

Environmental

Environment	Indendør

Regulatory

Certification	EN54-5

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57