PA25/3L

Conventional remote indicator

Product overview

The PA25/3L remote indicator is designed for direct connection to Kilsen fire detectors, enabling luminous indication outside the area where the detector is installed.

Configuration

The PA25/3L is supplied with a back box for surface mounting. It has two inlets for pipes of up to 20 mm in diameter. For recessed (flush) mounting, a universal mounting box with 60 mm screws and a minimum depth of 25 mm can be used.

Installation and use

The indicator should always be installed in an easily visible location. It is normally connected directly to the remote indicator terminals of the fire detector. Its high-luminous red LED indicators light up on activation.

The PA25/3L may be used with both addressable and conventional Kilsen fire detectors. It operates in the same way in both applications. In conventional applications only 1 of 3 LED indicators are lit to limit the power requirements.



Details

- Modern and elegant design
- Plastic casing with ruby red polycarbonate "spy-hole" reflector
- Large angle of visibility, lit up on four sides
- High luminosity
- Direct two-wire connection
- Wide power supply range makes it suitable for many applications
- Shock resistant
- Compatible with third party products

PA25/3L
Conventional remote indicator

Technical specifications

General

Compatibility	Excellence and Kilsen series detectors
Addressing method	Geen adressering vereist
Monitoring	Unmonitored
System support	Excellence & Kilsen series as well as 3rd party systems

Electrical

Power supply type	VDC
Operating voltage	5 to 10 VDC (on addressable systems) 2 to 5 VDC (on conventional systems)
Current consumption	<50 mA
Number of connection terminals	3
Cable specification	2-core

VID

Colour	Red

Physical

Physical dimensions	80 x 80 x 42 mm (W x H x D)
Net weight	10 g
Colour	Hvid
Mounting type	Loftmontering, Vægmontering
Mounting base	Shallow
Material	ABS

Environmental

Vandal proof	No
Operating temperature	-10 to +55°C
Storage temperature	-10 to +70°C
Environment	Indendør
IP rating	IP30

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CNBOP

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 6 October 2026 - 9:38