BS111N

Battery, 6 V, 10 Ah



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS111N

Battery, 6 V, 10 Ah

Technical specifications

General

Product type	Forseglet blybatteri

Electrical Characteristics

Nominal voltage	6 V
Nominal capacity	10 Ah
Internal approx. resistance	7 mOhm

Charge / discharge

Max. charge voltage	6.9 VDC at +20°C
Max. charge current	3 A
Max. discharge current	50 A

Physical

Physical dimensions	151 x 50 x 94 mm
Net weight	2.082 kg
Shipping weight	2.082 kg
Colour	Ciemnoszary
Material	ABS
Terminal type	Fast-on 4.8 mm

Environmental

Fire retardant	No
Vandal proof	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

Regulatory

Compliancy	CE, RoHS 2, WEEE

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 21 January 2026 - 19:53