# ATS1473-5

## 5 pack of ATS Proximity keyfob

### Product overview

Polycarbonate keyfob, for the ATS proximity readers. The reading distance is between 0 to 30 cm and it depends on the reader design.



### Details

- Read/Write capability
- Ability to program a unique 4-billion, 4-byte security code
- 4 memory areas for credit applications

# ATS1473-5

## 5 pack of ATS Proximity keyfob

## Technical specifications

### System

| | |
|---|---|
| Reading distance | 0 to 30 cm |
| Custom data model | No |
| Supported readers | Czytniki zbliżeniowe ATS |

### Technology

| | |
|---|---|
| Credential type | Nærhed |
| Credential operating frequency | 125 KHz |
| Supported technology 125 kHz | HiTag 2 |

### Printing

| | |
|---|---|
| Direct surface printing | No |

### Ordering information

| | |
|---|---|
| Minimum order quantity | 1 |
| Cards/tags in package | 5 |

### Physical

| | |
|---|---|
| Material | Polycarbonat |
| Form factor | Wieszak do klucza |
| Physical dimensions | 31 x 40 x 5 mm |
| Colour | Sort |

### Environmental

| | |
|---|---|
| Operating temperature | -25 to +50°C |
| IP rating | IP67 |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:24