TVN-1204CS-1T

TruVision NVR 12, 4 channels, 4 channel PoE, 40 Mbps, 1 TB

Reasons to choose TVN 12

The TVN 12cS recorder series offers a full-featured, compact recording solution for IP cameras with a maximum resolution of 8 MP(4K).
The TVN-1204cS is a cost-effective, easy-to-use recorder capable of recording up to four IP cameras, connected to the built-in PoE ports or via the LAN network.

Easy to use

A setup wizard with auto detection of IP cameras guarantees a fast installation of the recorder.
The TVN 12cS can be added to the internet without port forwarding or VPN, thanks to the built-in UltraSync connectivity. Showing remote video on mobile applications was never easier.
In combination with dedicated TruVision cameras that can support people and/or vehicle detection, the TVN 12 recorder series can find relevant events faster and without efforts.

Applications

The TVN 12cS is the ideal recording solution for small commercial and residential applications, where ease of use and fast deployment time are important.



Details

- Linux embedded Plug and Play configuration
- Supports H.264, H.265 and H.265+ encoding, depending on the cameras
- Four Plug & Play PoE Ports (PoE-af & PoE-at support) with a maximum resolution of 4K (8 MP)
- Automatic setup of IP addresses through Plug&Play PoE ports
- Up to 40 Mbps camera recording bandwidth for maximum four IP cameras
- 1 TB embedded storage
- Real time recording (Up to 4 MP)
- HDMI/VGA monitor output
- TruVision IP camera auto-detection
- IP camera configuration import/export
- UltraSync support for remote access without port forwarding
- Motion detection and VCA support, depending on the cameras
- Dedicated people/vehicle detection in combination with supported cameras
- Third party camera support via ONVIF Profile S or RTSP (custom protocols)
- Integration of Aritech IP intrusion panels via SIA/XSIA reporting
- TVK-600 IP keypad
- USB DVD burner support
- Full browser-, OSD- and software-based access for live, recorded video & configuration
- TVRMobile app for iOS and Android for remote viewing
- TruVision Navigator client/host or standalone application support
- External integration through SDK

TVN-1204CS-1T

TruVision NVR 12, 4 channels, 4 channel PoE, 40 Mbps, 1 TB

Technical specifications

General

Technology	IP
Operating system	Embedded Linux
Rack mountable	Nej

Video/audio input

Camera channels	4
IP camera channels	4
Camera bandwidth	40 Mbps
Audio compression	G.711alaw, G.711ulaw, G.722, G.726
Max. IP audio in	4
Max. analog audio In	1
Supported video compression standards	H.264, H.265, H.265+
Supported video streaming standards	Onvif, RTSP Custom Protocols

Local viewing

HDMI output	1
HDMI version	1.4, 2.0
VGA output	1
Max. local output resolution	4K
Synchronous playback OSD (channels)	Up to 4 channels (1080P)

Remote viewing

Total available viewing bandwidth	80 Mbps
Max. live viewing streams	128 streams
Max. playback viewing streams	8 streams
Max. simultaneous playback web browser	Up to 8 channels
Reverse playback web browser (channels)	Up to 8 channels
UltraSync support	Yes, embedded
Software compatibility	Advisor Management Software (ATS8600), TruVision Navigator, TVRmobile
Browser compatibility	Google Chrome, Internet Explorer, Mozilla Firefox, Safari

Storage

Storage capacity	1 TB
SATA interfaces	1
Max. capacity per SATA HDD (TB)	8
Maximum recording resolution	4 K
Recording modes	Continuous, Event, Ręczny
External storage	NAS
Edge failover recording	Yes

Networking

Network interface cards (NIC)	1
NIC type	RJ-45 10/100 Mbps self-adaptive Ethernet interface
PoE ports	4
Total PoE budget	50 W
PoE standards supported	PoE-af, PoE-at
Max. PoE budget per port	≤ 30 W
Plug & Play PoE support	Yes
Flexible PoE allocation	Yes
DNS support	DDNS, ezDDNS, Ingen IP
HTTPS support	Yes

External interfaces

USB interface back	1
USB interface front	1
Alarm inputs	4
Alarm outputs	1
Max. analog audio outputs	1

Electrical

Operating voltage	48 VDC
Power supply type	48 VDC
Power consumption without HDD (W)	≤65 W

Physical

Physical dimensions	320 x 240 x 48 mm (W x D x H)
Net weight	1.2 kg
Colour	Sort

Environmental

Operating temperature	-10 to +55°C
Relative humidity	10 to 90% noncondensing

Regulatory

Compliancy	CE, FCC, RCM, REACH, RoHS, UKCA, UL, WEEE

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 24 August 2026 - 15:00