DT713-5

Rivelatore termico/termovelocimetrico convenzionale serie 700

Generalità

The 700 series conventional detector line includes a range of temperature detectors:

- The DT713-5 is a class A2 temperature detector with a fixed temperature threshold of 57°C and built in rate-or-rise functionality.
- The DT713-5R has the same specifications as the DT713-5, but in addition includes a built in potential free changeover relay
- The DT713-7 is a class B temperature detector with a fix temperature threshold of 70°C and built in rate-or-rise functionality.



DT713-5

Rivelatore termico/termovelocimetrico convenzionale serie 700

Specifiche tecniche

Electrical

Power supply type	Zasilanie strefowe

Detection

Alarm temperature (typical)	+57°C ± 1.5°C

Physical

Colour	Śnieżnobiały (RAL 9001)
Mounting type	Loftmontering
Material (body)	Plastic

Environmental

Vandal proof	No
Application temperature (typical)	+25°C
Environment	Indendør

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Prodotti compatibili

Categoria	Riferimento	Descrizione
Detection device	DB702	Base con 6 terminali per serie 700.
Notification device	AI672	Ripetitore luminoso di allarme a led.
Notification device	AI673	Ripetitore luminoso di allarme a led con buzzer.

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57