ATS1459

(5 PACK) Secure ATS Ultra Keyfob

Product overview

The ultra keyfob in black color offers a robust solution for a secure environment where card data is protected with Mifare Desfire EV2 encryption. It can be used in secure mode with ATS118x range readers and ATS1136 keypad.
When used on other Mifare Readers the standard Mifare 7-byte CSN is provided instead of the secure card data.



Details

- Attractive designed ultra keyfob
- Card data secured by AES encryption
- Mifare Desfire EV2 encrypted application

ATS1459
(5 PACK) Secure ATS Ultra Keyfob

Technische specificaties

System

Reading distance	Secure mode: between 1 - 5 cm Unsecure mode: between 2-5 cm Distance may vary based on reader
Custom data model	No
Memory size	2 kB
Supported readers	ATS ATS118x Secure Readers

Technology

Credential type	Smart card
Credential operating frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN)

Printing

Direct surface printing	No

Ordering information

Minimum order quantity	1
Cards/tags in package	5

Physical

Material	PA6
Form factor	Key Fob
Physical dimensions	77 x 18 x 26 mm
Net weight	15 g
Shipping weight	30 g
Colour	Black
Card Label	Serial number

Environmental

Operating temperature	-10 to +50°C

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57