# FE130MD

**Cerradura electromagnética de 2x3.000N, monitorizada, para superficie.**

## Description

Eco Line double magnetic lock 2 x 300 kgf. Surface mounted, monitored.

## Application

Medium Security applications for internal or external double leaf doors.

## Reliable Security

This state of the art electro-magnetic locking device provides positive, instantaneous door control. Filler plates, angle brackets, and other mounting adapters are available to satisfy a wide range of door and frame types and conditions.

## Safe operation

Our locking devices are inherently fail-safe, releasing instantly upon command or loss of power. With no moving parts to wear, stick or bind; no mechanical linkages to bend or break; and no bolt travel time or misalignment to raise concern, both unlocking and locking are always accomplished with ease and efficiency. As those electromagnetic locking devices function independently of any mechanical type locks, magnetic locks will not jeopardize the fire door rating of an opening.



## Detalles

- 2 x 300 Kgf holding power
- Monitored changeover
- No residual magnetism
- 12/24 V dc jumper selectable operation
- Mounts easily with a minimum of tools

# FE130MD

## Cerradura electromagnética de 2x3.000N, monitorizada, para superficie.

## Especificaciones técnicas

### General

| | |
|---|---|
| Product type | Fechos Megnéticos |

### Monitoring & status

| | |
|---|---|
| Monitored | Yes |
| LED indicator | Yes |
| Door status switch | No |
| Monitored changeover | Yes |
| Magnetic bond sensor | Yes |

### Physical

| | |
|---|---|
| Colour | Aluminium |

Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 12 November 2026 - 18:57