IO954N

Unidade IO Comutação Alimentação - Apollo (SA4700-103)

General

IO954N is the new mains switching input/output unit which contains one or more normally open contacts connected to a single pair of cables. It also provides a voltage free change over relay output capable of switching mains.

Mechanical Construction

The IO954N is available in the new faceplate style enclosure. It is designed to be surface mounted to the wall and consists of 3 parts:
- a back box with knock-outs for cable entry
- a PCB assembly
- a protective front cover

Ease of Installation

Improved design for ease of wiring meaning faster installation – unit can be fitted to back-box before wiring is connected. Colour coded terminal blocks for easier identification (green for loop wiring, yellow for mains wiring, grey for inputs and low voltage relays).



Detalhes

- Improved design for ease of wiring meaning faster installation
- Loop powered
- Contains one or more NO contacts connected on a single pair of cables
- Local LEDs signalling I/O and fault conditions
- Isolators within each device

IO954N

Unidade IO Comutação Alimentação - Apollo (SA4700-103)

Especificações técnicas

Electrical

Operating voltage	17 to 35 VDC

Physical

Physical dimensions	150 x 90 x 60 mm
Net weight	301 g

Environmental

Operating temperature	-40 to +70°C
Relative humidity	0 to 95% noncondensing
Environment	Drinnen

Regulatory

Certification	CPR, EN54-17, EN54-18

Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57